

GRP DECKING STRIPS

Easy-to-fit strips make slippery decking safer instantly



AREAS OF USE

- Wooden decking
- Walkways
- Jetties, pontoons and marine slipways
- Bridges

FEATURES

- Waterproof, rotproof and will not warp
- Easy fit, all items preformed. Glue or screw fix, pre-drilled for easy fixing to timber and with all screws supplied
- Child friendly. Medium coarse option perfect for decks used by children or vulnerable adults
- Suitable for domestic and commercial decking (unsuitable for barefoot areas)
- Excellent slip resistance even in the wet
- Oil and chemical resistant
- Cut to size service available with no charge or can be trimmed on site using a hacksaw if required
- Ideal for wet or weak substrates which cannot be adequately prepared for paint
- Chamfered edges minimise trip hazards
- Helps meet the requirements of the DDA and 2004 Building Regulations

DESCRIPTION

Wooden decking and ramps can be hazardous in the wet or become slippery with algae in shady or damp conditions. Damp, slippery timber can be made safer instantly using Watco GRP Decking Strips. Glass Reinforced Plastic (GRP) strips come in two textures, medium and extra coarse, bringing security underfoot on unprotected decks. Watco GRP Decking Strips are suitable for use in both commercial and domestic areas and are especially effective in wet conditions. Holes are pre drilled at approximately 300mm intervals. One row of holes is drilled in the 50mm and 90mm wide strips, two rows in the 120mm width. Holes are 50mm in from each end. Screws are supplied for fixing to timber. Medium Grade Decking Strips are supplied in 1200mm and 2400mm lengths and 50mm or 90mm widths. They are designed for areas of decking mainly used by children or vulnerable adults.

SPECIFICATION

Dimensions for Medium Grade strips	1200mm x 50 & 90mm 2400mm x 50 & 90mm
Dimensions for Coarse Grade strips	1200mm x 50, 90 & 120mm 2400mm x 50, 90 & 120mm
Primer Required	No.
Usage Interior/ Exterior	Exterior.
Suitable For	Wood.
Grades	Medium & Coarse
Pack Size	Packs of 10.

Cut to size service	Yes
Oil & chemical resistant	Yes
Lightweight.	Yes
Non sparking	Yes
Non metallic	Yes
Fixing	Just lay the strip onto the wooden decking and fix using an appropriate screw. When drilling the strip it is not necessary to countersink the hole.







COLOURS



Samples are available on request. While great care is taken with the colour samples shown, no guarantee can be given that they represent exactly the colours offered.

GRADES & SLIP RESISTANCE

Watco GRP Decking Strips are available in 2 grades

 Medium Grade Low slip potential Wet PTV 71   	 Extra Coarse Grade Extremely low slip potential Wet PTV 80 
---	---

The UK Slip Resistance Group guide to slip resistance of a floor for able bodied pedestrians:

Four S Pendulum Value	Potential for Slip
Above 65	Extremely Low
35 to 65	Low
25 to 35	Moderate
25 and Below	High

Slip resistance levels measured using the Pendulum Test method (WF rubber slider) – certificate available on request. To ensure that the above slip resistant levels are maintained the strips should be kept clean.



WATCO.CO.UK