

Exit LED

Indoor LED exit sign

Whitecroft
lighting

IP20

LED



Optics

- Power consumption:
 - 3W maintained
 - 1.5W non maintained
- 16 x low energy LEDs
- 34m viewing distance
- Product is supplied as a complete unit with opal polycarbonate legend panel already fitted
- Up, down, left and right legend panels are available
- Legends supplied in accordance with BS 5266-1 2011 (ISO7010)

Body

- Wall mounted via key hole slot fixings
- Steel body finished white
- Two part body for ease of installation, cover hooks over the back plate and is simply retained below
- High temperature Ni-Cd battery with constant current charger and LED charge indicator
- 3 hour maintained (may be wired as non-maintained)
- BESA cable entry

Order codes

3W, with UP legend supplied	EXM7010U
3W, with LEFT legend supplied	EXM7010L
3W, with RIGHT legend supplied	EXM7010R
3W, with DOWN legend supplied	EXM7010D

Options

COMEPS	Add suffix /EP	i.e EXM7010U/EP
--------	----------------	-----------------

Dimensions

L	W	H	KG
385	71	185	2.4

To Specify

3W LED IP20, 3 hour self-contained maintained emergency exit sign with rigid white powder coated steel body and opal polycarbonate legend. High temperature Ni-Cd battery with constant current charger and LED charge indicator - as Whitecroft Lighting EXIT LED