

Kolo Suspended

High efficiency suspended luminaire

Whitecroft
lighting

120+
LL/CW



ECA

IP44

LED



Without Trim Ring

Overview

Kolo brings style and efficiency to any application. With a host of optional attachments to add visual interest, Kolo is the optimum lighting solution.

Optics



- Nominal light output options:
 - 300mm \varnothing
 - 800 lumens, 6W
 - 1100 lumens, 9W
 - 400mm \varnothing
 - 1700 lumens, 14W
 - 2300 lumens, 19W
 - 2700 lumens, 21W
 - 3500 lumens, 28W
- Emergency Output (BLF):
 - 300mm - 360 Lumens
 - 400mm - 500 Lumens
- Polycarbonate opal diffuser
- Available with 3000K and 4000K LED

Body





- 300mm or 400mm diameter bodies in cast aluminium with injection moulded base
- Finished in white or silver
- IP44
- Choice of integrated emergency options:
 - 3 hour emergency
 - EasyTest
 - COMEPS
- Optional Command 5 microwave detector mounted behind the diffuser that can be set to one of two configurations;
 - Microwave presence detection with ON/OFF operation
 - Microwave presence detection with High/Low/Off set-back functionality. Can be set to switch from 100% down to set-back position of 50%, 30%, 20%, 10% or OFF
- Optional trim ring available for an alternative aesthetic finish (supplied separately)
- Product also available as surface and IP65

Order codes

IP44 300mm Silver (4000K)

				B50		
IP44 300mm Silver	Fixed Output	3hr Emergency	LL/CW	L70	L80	L90
806 lumens (6.3W)	K4H364KS	K4H364KSEM	 128	>100k	>100k	>100k
1136 lumens (8.8W)	K4H3124KS	K4H3124KSEM	 129	>100k	>100k	92k

IP44 400mm Silver (4000K)

				B50		
IP44 400mm Silver	Fixed Output	3hr Emergency	LL/CW	L70	L80	L90
1755 lumens (13.7W)	K4H4154KS	K4H4154KSEM	 128	>100k	>100k	100k
2359 lumens (18.5W)	K4H4204KS	K4H4204KSEM	 128	>100k	>100k	95k
2793 lumens (21.3W)	K4H4274KS	K4H4274KSEM	 131	>100k	>100k	87k
3549 lumens (27.7W)	K4H4354KS	K4H4354KSEM	 128	>100k	>100k	75k

Accessories

Suspension Kit	KLSUSKIT
Trim Ring 300mm Silver	KLTR300S
Trim Ring 400mm Silver	KLTR400S

Options

COMEPS	Add suffix /EP	i.e K4H3124KS/EP
COMMAND 5 *	Replace H with Q5	i.e K4Q53124KS
DALI DIMMING	Replace H with Y	i.e K4Y3124KS
WHITE FINISH	Replace S with W	i.e K4H3124KW


* Command 5 not available in 300mm emergency or DALI products

For 3000K colour temperature, please contact Whitecroft

LED Performance


Colour Temp	RA (CRI)	Colour consistency
4000K	>80	MacAdam 3 SDCM

Dimensions




VERSION	H	KG	KG(EM)	Ø
300mm suspended	95	2.1	2.5	300
400mm suspended	95	3.5	3.9	400

Photometric Performance




300mm \varnothing 6.3W
806 Lumens
LOR = 100.0%
SHR MAX = 1.64



400mm \varnothing 13.7W
1755 Lumens
LOR = 100.0%
SHR MAX = 1.64

Performance Guide



Lamps	19W LED
Illuminance	200 lux
Spacing	3.0m x 3.0m
Maintenance	0.8
Reflectance	70/50/20
Ceiling Height	2.7m
Working plane	0.8m

To Specify

Suspended circular IP44 LED luminaire in 300 or 400mm diameter. Polycarbonate opal diffuser. Optional integrated microwave presence detector with ON/OFF or set-back functionality - as Whitecroft Lighting KOLO SUSPENDED