

# Pathfinder High Level LED Head

Whitecroft  
lighting

High output emergency luminaire head

IP20

IP40

LED



Surface Mounted, Silver

## Optics

- High performance, high output LED emergency luminaires supplied complete with driver
- Only for use with emergency Pathfinder system
- Specifically designed for application in areas that require high level mounting; e.g. plant rooms, atrium, warehouses etc.
- High output of 260 lumens
- 4100K 'cool' white colour temperature

## Body

- Recessed and surface mounted options
- For mounting up to 10m high
- Cast aluminium body with integral heat sink
- Finished in white or silver
- Supplied complete with driver
- Input voltage 24V DC via Pathfinder system
- 5W total power including driver
- Current consumption: 0.2A
- Recessed IP20
- Surface IP40

# Order codes

## Version

Surface, 5W, white	PFDHSDLW
Recessed, 5W, white	PFDHRDLW


## Options

SILVER	Replace W with S	i.e PFDHRDLS
--------	------------------	--------------


# Dimensions

VERSION	H	KG	Ø	CAØ
Surface	41	0.3	85	
Recessed	30	0.2	85	68

# Performance Guide



Mounting Height	Distance from wall
3m	5.3
5m	6.3
7m	6.7
10m	6.2



Mounting Height	Distance Between Heads
3m	12.9
5m	15.9
7m	17.7
10m	19.1

# To Specify

Central battery, central test LED emergency lighting system. Fully addressable LED emergency lighting points. Control unit with programmable interface – as Whitecroft Lighting PATHFINDER