

Pathfinder LED Exit Sign

Ceiling, wall or suspended exit sign

Whitecroft
lighting

IP20

LED



Optics

- 22m viewing distance - 6 x 0.5W LEDs
- LEFT, RIGHT, UP and DOWN printed acrylic legend panel to be ordered separately

Body

- Extruded aluminium body housing electronics and LEDs
- Three mounting options:
 - Ceiling
 - Wall
 - Suspended (Supplied with 1m wire suspension kit)
- Input voltage 24V DC
- Supplied complete with driver
- Consumption 0.125A

Note: LED exit sign can only be used as part of a Pathfinder system

Order codes

LED Exit Sign 22m

| | | |
|--------------|-----------------|------------------|
| 4 x 0.5W LED | Ceiling Mounted | PFDCEILING/22M |
| 4 x 0.5W LED | Suspended | PFDSUSPENDED/22M |
| 4 x 0.5W LED | Wall Mounted | PFDWALL/22M |

Legends - 22m

| | | |
|----------------|--------------|--------------|
| Down Legend | Double Sided | PFDLPDSD/22M |
| Left Legend | Single Sided | PFDLPSSL/22M |
| Right Legend | Single Sided | PFDLPSSR/22M |
| To Side Legend | Double Sided | PFDLPDST/22M |
| Up Legend | Double Sided | PFDLPDSU/22M |
| Up Legend | Single Sided | PFDLPSSU/22M |

* Legends to be ordered separately

Dimensions

| VERSION | L | W | H | KG |
|---------|-----|----|-----|-----|
| 22m | 256 | 28 | 180 | 0.9 |

To Specify

Central battery, central test LED emergency lighting system. Fully addressable LED emergency lighting points. Control unit with programmable interface – as Whitecroft Lighting PATHFINDER