

# Pathfinder LED Head

Whitecroft  
lighting

Pathfinder emergency luminaire head

IP68

LED



Surface Mounted



Escape Route Head



IP68 Head

## Optics

- High performance, LED emergency luminaires supplied complete with driver
- Recessed - Open area, escape route and IP68 options available
- Surface Mounted - Open area, escape route options available
- Robust, compact and low energy solution

## Body

- Cast aluminium body with integral heat sink
- Powder coated white or silver options
- Spring retaining clips for ceilings up to 16mm
- Input voltage 24V DC
- Supplied complete with driver
- Current consumption: 0.14A

Note: LED heads can only be used as part of a Pathfinder system

## Order codes

### Escape Route LED Head

Recessed LED Silver Body - 3w	PFDCCOLEDS
Recessed LED White Body - 3w	PFDCCOLEDW
Surface Mounted LED Silver Body -3w	PFDCCOLEDSSM
Surface Mounted LED White Body -3w	PFDCCOLEDWSM

### IP68

Recessed LED Silver Body IP68 - 3w	PFDRELEDS/IP68
------------------------------------	----------------


### LED Head

Recessed LED Silver Body - 3w	PFDRELEDS
Recessed LED White Body - 3w	PFDRELEDW
Surface Mounted LED Silver Body -3w	PFDRELEDSSM
Surface Mounted LED White Body -3w	PFDRELEDWSM


## Dimensions

Version	L	W	H	KG	Ø	CAØ
LED Head			50	0.1	55	46
Escape Route			25	0.1	55	46
IP68			53	0.1	31	26
Surface Mounted	140	140	42	0.5		


# Performance Guide




LED Head - Mounting Height	Distance from Wall
2.5m	2.4m
3.0m	2.6m
4.0m	3.1m



LED Head - Mounting Height	Distance between Heads
2.5m	5.6m
3.0m	5.8m
4.0m	7.0m



Escape Route LED Head - Mounting Height	Distance from Wall
2.5m	4.60m
3.0m	4.90m
4.0m	4.20m



Escape Route LED Head - Mounting Height	Distance between Heads
2.50m	10.90m
3.00m	12.10m
4.00m	12.20m

## To Specify

Central battery, central test LED emergency lighting system. Fully addressable LED emergency lighting points. Control unit with programmable interface – as Whitecroft Lighting PATHFINDER