

LOW ENERGY



4000K
NEUTRAL WHITE



5 YEAR*
WARRANTY



IP20/IP40



IK08



CRI
>80





OP. TEMP
-20°C
to
+40°C



VOLTAGE
AC220 - 240V



2 point wire suspension kit is available



- Steel powder coated body with low profile opal diffuser.
- IP40 from below and IP20 from above.
- Suitable for ceiling mounting or suspension.
- Available with dimmable driver for connection to a remote sensor.
- On/Off integral sensor available.

Code	Watts	Delivered lumens	Lumens per Watt	L (mm)	W (mm)	D (mm)	A* (mm)	Weight (kg)
SSL204A	20	2090	100	1184	208	70	1066	3.9
SSL404A	40	4180	102	1184	208	70	1066	4.0
SSL305A	30	3135	101	1484	208	70	1366	4.2
SSL605A	60	6270	101	1484	208	70	1366	4.4
SSL406A	40	4180	102	1784	208	70	1666	4.5
SSL806A	80	8360	101	1784	208	70	1666	4.7

Optional Features (add suffix to order code)

/M3: 3hr integral emergency

/HMS: On/Off integral microwave sensor

/LSLV: Dali driver

FAC/SUSP/3M: 3m wire suspension kit

* These dimensions are used for the suspension kits