

# GTB65

Ultimate High Specification Weatherproof




INDUSTRIAL LIGHTING



STAINLESS STEEL CLIPS

- High specification GRP housing for ultimate product durability in tough environments.
- Developed to provide the highest luminaire efficacy in 4ft and 5ft variants.
- Stainless steel clips supplied as standard.
- 4000K as standard also available in 2700K, 3000K, 5000K and 6500K.
- Opal PMMA diffuser to create a uniform and diffused spread of light.
- Available with **EyeWi** wireless controls.



A = Fixing centres  
C = Hanger positions



Code	Watts	Delivered lumens	Lumens per Watt	L (mm)	W (mm)	D (mm)	A (mm)	C (mm)	Weight (kg)
GTB32/4K	22	3201	146	1277	116	99	800	700	4.2
GTB64/4K	44	6403	146	1277	116	99	800	700	4.2
GTB33/4K	23	3361	146	1577	116	99	1100	1000	5.8
GTB46/4K	33	4614	140	1577	116	99	1100	1000	5.8
GTB67/4K	45	6724	149	1577	116	99	1100	1000	5.8
GTB92/4K	65	9229	141	1577	116	99	1100	1000	5.8

**Optional Features** (add suffix to order code)

- /M3: 3hr integral emergency (\* not suitable for use below 0°C)
- /HM11: Microwave sensor for On/Off
- /FM11: 100%/10% (never off) dimming with integral microwave sensor
- /LP55: Dimming control with **EyeWi** wireless control and integral PIR (IP54 rated)
- /LS36: Dimming control with **EyeWi** wireless control and integral microwave (IP65 rated)
- /W3: Self-test wireless reporting 3hr emergency (\* not suitable for use below 0°C)

Designed & manufactured to comply with EN 60598 and are CE certified.

Luminaire is not designed to be mounted in full external conditions- please speak to the Wirefield sales office for further information.