

# WOODPECKER

NATURALLY INSPIRED FLOORING

## TECHNICAL DATA & APPLICATION

### ACOUSTAMAT

Woodpecker Acoustamat is a slatted, polyethylene foam underlay that enables planks to be glued directly to the subfloor using a liquid batten system. The precut slots ensure minimum adhesive is used and allow for spot levelling. Once installed, Acoustamat provides a reliable acoustic barrier.



#### TECHNICAL DATA

MATERIAL .....	Cross-linked polyolefin foam
COLOUR .....	Green
THICKNESS .....	3mm
COVERAGE .....	16.5m <sup>2</sup>
MAX LOAD .....	250kg/m <sup>3</sup>
COMPRESSIVE STRENGTH .....	2800kg/m <sup>3</sup>
DENSITY .....	Approx 20kg/m <sup>3</sup>
THERMAL RESISTANCE .....	0.09 m <sup>2</sup> K/W
IMPACT SOUND REDUCTION .....	16dB
UNDERFLOOR HEATING .....	Yes
OPERATING TEMPERATURE .....	-50°C to 100°C
MOISTURE BARRIER .....	No
FIRE RETARDANT .....	Yes

#### SPECIFICATION DISCLAIMER

This technical data sheet was written by Woodpecker Flooring and at the time of writing and publication, all information was specified correctly. The company reserves the right to change specification without notice. Customers should confirm that the product is still available with the specification shown.

Woodpecker House, 29 Pant Glas Industrial Estate, Bedwas, Caerphilly CF83 8DR

T: 02920 888 223 F: 02920 881 694 [info@woodpeckerflooring.co.uk](mailto:info@woodpeckerflooring.co.uk)

[WWW.WOODPECKERFLOORING.CO.UK](http://WWW.WOODPECKERFLOORING.CO.UK)