

WOODPECKER

NATURALLY INSPIRED FLOORING

TECHNICAL DATA & APPLICATION

AQUASTOP

Designed especially for ground level subfloors where moisture could be present, Aquastop is a foam underlay which incorporates a laminated damp proof membrane (DPM). The membrane is 80mm wider than the underlay padding to ensure ultimate moisture protection when installed. Aquastop's low thermal resistance is ideal for underfloor heating too. It's produced from closed cell Polyethylene Foam which is CFC and HCFC free, and 100% recyclable.



TECHNICAL DATA

COLOUR	Green
THICKNESS	3mm
ROLL SIZE	1m x 15m
COVERAGE	15m ²
ROLL WEIGHT	168.03 g/m ²
DENSITY	30 kg/m ³
TOG RATING	0.67
THERMAL CONDUCTIVITY	0.045 W/mK
ACOUSTIC PROPERTIES	19 dB
UNDERFLOOR HEATING	Yes
MOISTURE BARRIER	No
BACKING	Clear LDPE 40µm

SPECIFICATION DISCLAIMER

This technical data sheet was written by Woodpecker Flooring and at the time of writing and publication, all information was specified correctly. The company reserves the right to change specification without notice. Customers should confirm that the product is still available with the specification shown.

Woodpecker House, 29 Pant Glas Industrial Estate, Bedwas, Caerphilly CF83 8DR

T: 02920 888 223 F: 02920 881 694 info@woodpeckerflooring.co.uk

WWW.WOODPECKERFLOORING.CO.UK