

WOODPECKER

NATURALLY INSPIRED FLOORING

TECHNICAL DATA & APPLICATION

BASIC 20

Where you have a level and moisture-free subfloor, Basic 20 underlay is the optimum choice. It's inexpensive, offers good comfort and support, and has reasonable soundproofing qualities. Its low thermal resistance is great for underfloor heating too.

Basic 20 is produced from close cell Polyethylene Foam which is CFC and HCFC free, and 100% recyclable.



TECHNICAL DATA

MATERIAL	Polyethylene
COLOUR	Green
THICKNESS	3mm
ROLL SIZE	1m x 15m
COVERAGE	15m ²
ROLL WEIGHT	129.016 g/m ²
DENSITY	30 kg/m ³
TOG RATING	0.72
ACOUSTIC PROPERTIES	19dB
THERMAL CONDUCTIVITY	0.045 W/mK
UNDERFLOOR HEATING	Yes
MOISTURE BARRIER	No

SPECIFICATION DISCLAIMER

This technical data sheet was written by Woodpecker Flooring and at the time of writing and publication, all information was specified correctly. The company reserves the right to change specification without notice. Customers should confirm that the product is still available with the specification shown.

Woodpecker House, 29 Pant Glas Industrial Estate, Bedwas, Caerphilly CF83 8DR

T: 02920 888 223 F: 02920 881 694 info@woodpeckerflooring.co.uk

WWW.WOODPECKERFLOORING.CO.UK