

WOODPECKER

NATURALLY INSPIRED FLOORING

TECHNICAL DATA & APPLICATION

BLUE DAMP PROOF BARRIER

This superior quality, impermeable underlay is designed to protect flooring from a damp subfloor. Its dimpled surface allows air to flow beneath the barrier making it perfect for basements or recently screeded floors. The product allows a new subfloor to dry without delaying installation.



TECHNICAL DATA

RAW MATERIAL	Polypropylene
COLOUR	Blue
THICKNESS	0.5mm
STUD HEIGHT	Approx 2.0mm
ROLL SIZE	2.05m x 20m
COVERAGE	38m ²
WEIGHT	450 g/m ²
TOG RATING	1.5
ACOUSTIC PROPERTIES	approx. 17dB (with 14mm parquet) approx. 19dB (with 7mm laminate flooring)
SHOCK CUSHIONING	approx 20% (DIN 18032 part 2)
THERMAL CONDUCTIVITY	0.22 W/mK
WATER VAPOUR RESISTANCE	1500 m ² .s Gpa/kg, or 300m equivalent air layer
FLAMMABILITY	B2 (DIN 4102)
UNDERFLOOR HEATING	Yes
MOISTURE BARRIER	Yes

STORAGE:

Rolls should be stored upright.

SPECIFICATION DISCLAIMER

This technical data sheet was written by Woodpecker Flooring and at the time of writing and publication, all information was specified correctly. The company reserves the right to change specification without notice. Customers should confirm that the product is still available with the specification shown.

Woodpecker House, 29 Pant Glas Industrial Estate, Bedwas, Caerphilly CF83 8DR

T: 02920 888 223 F: 02920 881 694 info@woodpeckerflooring.co.uk

WWW.WOODPECKERFLOORING.CO.UK