

# WOODPECKER

NATURALLY INSPIRED FLOORING

## TECHNICAL DATA & APPLICATION

# COLOUR SEALANT

Woodpecker Colour Sealant is handy for sealing edges and covering gaps when fitting wood flooring. It can be blended with the colour of the floor to achieve a beautiful and professional finish.

### APPLICATION:

Surfaces must be clean, dry and free from grease and dust. Cut the cartridge tip and screw on the nozzle. Cut the nozzle to the desired diameter at a 70°C angle. Allow to dry following application.

The sealant can be overpainted or varnished within approximately one hour of application. Uncured product can be cleaned with water. Once cured, the product can be removed mechanically.

## TECHNICAL DATA

BASE .....	Acrylic Resin
CURING SYSTEM .....	Water dispersion
CURING TIME AT 20°C .....	Approx. 60 minutes
CARTRIDGE SIZE .....	300ml
BROOKFIELD VISCOSITY .....	Paste
SPECIFIC GRAVITY .....	1.06
ELONGATION AT BREAK .....	1184%
MODULUS AT 100% (ISO 37) .....	0.09 N/mm <sup>2</sup>
TENSILE STRENGTH (ISO 37) .....	0.12 N/mm <sup>2</sup>

### STORAGE:

Shelf life 5 years in dry conditions between 5°C and 30°C.

### SPECIFICATION DISCLAIMER

This technical data sheet was written by Woodpecker Flooring and at the time of writing and publication, all information was specified correctly. The company reserves the right to change specification without notice. Customers should confirm that the product is still available with the specification shown.

Woodpecker House, 29 Pant Glas Industrial Estate, Bedwas, Caerphilly CF83 8DR

T: 02920 888 223 F: 02920 881 694 [info@woodpeckerflooring.co.uk](mailto:info@woodpeckerflooring.co.uk)

[WWW.WOODPECKERFLOORING.CO.UK](http://WWW.WOODPECKERFLOORING.CO.UK)