

WOODPECKER

NATURALLY INSPIRED FLOORING

TECHNICAL DATA & APPLICATION

FLOORMATE

Floormate provides excellent moisture protection and is ideal for areas with heavy foot traffic. Made from high performance rubber, it incorporates a foil vapour barrier to prevent migration of moisture from the subfloor. The product combines comfort and support with great sound and thermal insulation.



TECHNICAL DATA

MATERIAL.....	Rubber
COLOUR.....	Pale Brown
THICKNESS.....	3.6mm
WEIGHT.....	25 or 38kg
COVERAGE.....	10 or 15m ²
TOG RATING.....	0.55
IMPACT SOUND REDUCTION.....	23dB
TENSILE STRENGTH (LENGTHWISE).....	800kPa
TENSILE STRENGTH (CROSSWISE).....	600kPa
UNDERFLOOR HEATING.....	No
MOISTURE BARRIER.....	Yes

SPECIFICATION DISCLAIMER

This technical data sheet was written by Woodpecker Flooring and at the time of writing and publication, all information was specified correctly. The company reserves the right to change specification without notice. Customers should confirm that the product is still available with the specification shown.

Woodpecker House, 29 Pant Glas Industrial Estate, Bedwas, Caerphilly CF83 8DR

T: 02920 888 223 F: 02920 881 694 info@woodpeckerflooring.co.uk

WWW.WOODPECKERFLOORING.CO.UK