

WOODPECKER

NATURALLY INSPIRED FLOORING

TECHNICAL DATA & APPLICATION

LEVEL-X PRIMER

A highly advanced styrene-butadiene based polymer designed to stabilise and prepare substrates ready for the application of adhesives and levelling compounds. Level-X is designed to increase adhesion, durability, water resistance and strength.

TECHNICAL DATA

MATERIAL..... Water based styrene-butadiene polymer

PACK SIZE..... 1 litre

COVERAGE..... 1 litre applied neat = 10m²

1 litre diluted with 3 parts water = 40m²

1 litre applied as a slurry coat = 18m²

APPLICATION TEMPERATURE..... Between 5°C and 35°C

DRYING TIME BEFORE TILING..... 30 - 45 minutes in ideal conditions.

The drying/curing time will depend on the porosity of the substrate and ambient conditions/temperatures

STORAGE..... Store unopened, clear of the ground in cool, dry conditions.

SHELF LIFE..... Stored correctly this product has a shelf life of 12 months.

COLOUR..... Light green

PREPARATION:

Surfaces must be sound and free from contaminants. Any laitance or surface treatments must be removed before use. Concrete, anhydrite screeds and power



floated concrete must be fully cured and any dust removed by vacuum. The temperature of the substrate must be above 5°C when Level-X Primer is applied. Underfloor heating must be switched off 2 days before application. In some cases, a damp proof membrane may also be required.

APPLICATION:

Shake well before use. Apply evenly to the whole surface with a paint roller or brush. Please note that the coverage will be less with a roller. Wash tools after use with warm water. Allow approximately 1 hour in good conditions to fully dry. Avoid excessive traffic immediately after drying.

ANHYDRITE SCREED: Apply one coat diluted 3 parts water to 1 part primer and allow to dry. Follow with a second undiluted/heat coat.

CONCRETE, SAND AND CEMENT SCREEDS, BRICK, BLOCK, CEMENT BOARDS, PLASTER, DRY LINING: Apply one coat diluted 3 parts water to 1 part primer. NB: Plaster will require a second undiluted coat, if a cement-based product is being applied.

TIMBER, PLYWOOD, UNDERFLOOR HEATING, FIBREGLASS: Apply undiluted primer to all exposed edges and joints and allow to dry. Apply one coat diluted 2 parts water to 1 part primer.

QUARRY TILES, TERRAZZO, NATURAL STONES: Apply one coat diluted 3 parts water to 1 part primer.

CERAMICS, VINYL, ASPHALT, BITUMEN: Apply one coat diluted 1 part water to 1 part primer mixed with a little neat cement to form a slurry.

STEEL: Abrade the surface and apply one coat diluted 1 part water to 1 part primer.

COVERAGE:

1 litre neat Level-X Primer = 10 square metres.

STORAGE:

Store unopened in dry conditions. Protect from frost.

SPECIFICATION DISCLAIMER

This technical data sheet was written by Woodpecker Flooring and at the time of writing and publication, all information was specified correctly. The company reserves the right to change specification without notice. Customers should confirm that the product is still available with the specification shown.

Woodpecker House, 29 Pant Glas Industrial Estate, Bedwas, Caerphilly CF83 8DR

T: 02920 888 223 F: 02920 881 694 info@woodpeckerflooring.co.uk