

WOODPECKER

NATURALLY INSPIRED FLOORING

TECHNICAL DATA & APPLICATION

SOLITEC

This specialist underlay has a strong adhesive top layer that provides a bond for floated solid wood or engineered wood floors. Made from high quality, crosslinked polyethylene foam with a close cell structure, the underlay is moisture-proof, provides a high standard of comfort and evens out slight surface irregularities. It's great for use in rooms with a normal level of traffic, offering good sound insulation.



TECHNICAL DATA

MATERIAL.....	Polyethylene
COLOUR	Green
THICKNESS	3mm
COVERAGE.....	10m ²
DENSITY.....	Approx 30kg / m ³
THERMAL RESISTANCE	0.084 m ² K/W
THERMAL CONDUCTIVITY.....	0.036 W/m K
IMPACT SOUND REDUCTION.....	20dB
UNDERFLOOR HEATING	Yes
MOISTURE BARRIER	No
COMPRESSIVE STRENGTH	28 kPA 2800 kg/m ²
TENSILE STRENGTH (LENGTHWISE).....	0.41 N/mm ²

STORAGE

Do not store outdoors, protect from exposure of sunlight.

SPECIFICATION DISCLAIMER

This technical data sheet was written by Woodpecker Flooring and at the time of writing and publication, all information was specified correctly. The company reserves the right to change specification without notice. Customers should confirm that the product is still available with the specification shown.

Woodpecker House, 29 Pant Glas Industrial Estate, Bedwas, Caerphilly CF83 8DR

T: 02920 888 223 F: 02920 881 694 info@woodpeckerflooring.co.uk

WWW.WOODPECKERFLOORING.CO.UK