

# WOODPECKER

NATURALLY INSPIRED FLOORING

## TECHNICAL DATA & APPLICATION

# UNDERMATE

*This low tog, high performance rubber underlay is designed to withstand heavy foot traffic and provides maximum thermal transfer with underfloor heating. A damp proof membrane should be installed when using this underlay in underfloor heated rooms.*



## TECHNICAL DATA

MATERIAL.....	Rubber
COLOUR.....	Pale Brown
THICKNESS.....	3.6mm
WEIGHT.....	25kg
COVERAGE.....	10m <sup>2</sup>
TOG RATING.....	0.55
IMPACT SOUND REDUCTION.....	23dB
TENSILE STRENGTH (LENGTHWISE).....	800kPa
TENSILE STRENGTH (CROSSWISE).....	600kPa
UNDERFLOOR HEATING.....	Yes
MOISTURE BARRIER.....	No

## SPECIFICATION DISCLAIMER

*This technical data sheet was written by Woodpecker Flooring and at the time of writing and publication, all information was specified correctly. The company reserves the right to change specification without notice. Customers should confirm that the product is still available with the specification shown.*

Woodpecker House, 29 Pant Glas Industrial Estate, Bedwas, Caerphilly CF83 8DR

T: 02920 888 223 F: 02920 881 694 [info@woodpeckerflooring.co.uk](mailto:info@woodpeckerflooring.co.uk)

[WWW.WOODPECKERFLOORING.CO.UK](http://WWW.WOODPECKERFLOORING.CO.UK)