

WOODPECKER

NATURALLY INSPIRED FLOORING

TECHNICAL DATA & APPLICATION

XL UNDERLAY

When a subfloor suffers from some minor dips (up to 3mm), XL Underlay can help to solve the problem. It's made from lightweight extruded polystyrene and comes in packs of 10 tiles that are 500mm wide by 1200mm long. It offers excellent sound and thermal insulation, and when taped together forms an effective moisture barrier.



TECHNICAL DATA

MATERIAL	Extruded Polystyrene
COLOUR	Dark Grey
THICKNESS	6mm
DENSITY	32 kg/m ³
COVERAGE	6m ²
THERMAL CONDUCTIVITY	0.03 W/mK
IMPACT SOUND REDUCTION	19dB
UNDERFLOOR HEATING	Yes
MOISTURE BARRIER	Yes

SPECIFICATION DISCLAIMER

This technical data sheet was written by Woodpecker Flooring and at the time of writing and publication, all information was specified correctly. The company reserves the right to change specification without notice. Customers should confirm that the product is still available with the specification shown.

Woodpecker House, 29 Pant Glas Industrial Estate, Bedwas, Caerphilly CF83 8DR

T: 02920 888 223 F: 02920 881 694 info@woodpeckerflooring.co.uk

WWW.WOODPECKERFLOORING.CO.UK